



- Bright superior whiteness for a perfect reproduction of colours
- Exceptional bulk level and opacity thanks to its Eucalyptus Globulus fibre content
- A uniform surface with an excellent smoothness for optimum high-quality printability
- A natural touch & feel, ideal to give another dimension to all your day-to-day applications
- Environmentally friendly: ECF pulp, Green Star System™ with 4 stars, FSC® and European Ecolabel certifications



Print Speed®

Basis weight (g/m ²)	ISO 536	60	70	75	80	90	100	110	120	135	150	170	190	225	250	300	350	400
Brightness (%)	ISO 2470	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110
Whiteness (CIE)	ISO 11457	161	161	161	161	161	161	161	161	161	161	161	161	161	161	161	161	161
Roughness (ml/min)	ISO 8791-2	150	150	180	150	150	150	150	150	150	150	200	200	200	200	200	200	200
Opacity (%)	ISO 2471	87	91	92	94	95	96	97	98	98	98	99	99	99	99	99	99	99
Moisture (%)	ISO 287	6,20	6,20	6,20	6,00	6,00	5,80	5,80	5,80	6,50	6,50	6,50	6,50	6,50	6,50	6,50	6,50	6,50
Bulk (cm ³ /g)		1,33	1,31	1,33	1,33	1,29	1,28	1,28	1,25	1,26	1,26	1,26	1,29	1,29	1,29	1,35	1,35	1,35
Caliper (µm)	ISO 534	80	92	95	106	116	128	141	150	170	185	215	240	290	320	380	438	500



Discover all the Print Speed range at www.antalisis.com