

## BRISK TEXTURE NANO-DOT PURE WHITE

| 項 目                                                                                                      |    | 單位               | 120 g/m <sup>2</sup> | 140 g/m <sup>2</sup> | 170 g/m <sup>2</sup> | 200 g/m <sup>2</sup> | 240 g/m <sup>2</sup> | 290 g/m <sup>2</sup> | 測試方式     |
|----------------------------------------------------------------------------------------------------------|----|------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------|
| 基重 Basis Weight                                                                                          |    | g/m <sup>2</sup> | 128±4%               | 148±4%               | 178±4%               | 208±4%               | 248±4%               | 298±4%               | ISO 536  |
| 厚度 Thickness                                                                                             |    | μm               | 135±5%               | 165±5%               | 205±5%               | 245±5%               | 290±5%               | 360±5%               | ISO 534  |
| 水份 Moisture Content                                                                                      |    | %                | 5.5±1                | 5.5±1                | 5.5±1                | 5.5±1                | 5.5±1                | 5.5±1                | ISO 287  |
| 白度 Brightness                                                                                            |    | %ISO             | 95↑                  | 95↑                  | 95↑                  | 95↑                  | 95↑                  | 95↑                  | ISO 2470 |
| 抗張強度<br>Tensile Strength                                                                                 | MD | kg/15mm          | 8.0 ↑                | 9.0 ↑                | 11.0 ↑               | 12.0 ↑               | 14.0 ↑               | 16.0 ↑               | ISO 1924 |
|                                                                                                          | CD |                  | 4.5 ↑                | 6.0 ↑                | 7.0 ↑                | 8.0 ↑                | 9.0 ↑                | 9.5 ↑                |          |
| 表面強度<br>Picking                                                                                          | W  | A                | ≥10                  | ≥10                  | ≥10                  | ≥10                  | ≥10                  | ≥10                  | T459     |
|                                                                                                          | F  |                  | ≥10                  | ≥10                  | ≥10                  | ≥10                  | ≥10                  | ≥10                  |          |
| Note: The specification refers to an average of a composite sample according to our standard procedures. |    |                  |                      |                      |                      |                      |                      |                      |          |
| Not to be used for purposes other than what we specified. We reserve the right to modifications.         |    |                  |                      |                      |                      |                      |                      |                      |          |