

BRISK VOGUE

Fine and even surface with its own soft tactility, high color saturation and image restoration.

Surface : Surface Treated
Colour : Pure White

FSC™ Certified
Acid Free
Elemental Chlorine Free (ECF)
Suitable for digital print

Technical Specification

Characteristic		Unit	105gsm	120gsm	140gsm	170gsm	240gsm	290gsm	Test Method
Basic Weight		g/m ²	125±4%	125±4%	145±4%	175±4%	240±4%	295±4%	ISO 536
Thickness		µm	135±4%	135±4%	160±4%	200±4%	300±4%	360±4%	ISO 534
Moisture Content		%	5.5±1	5.5±1	5.5±1	5.5±1	5.5±1	5.5±1	ISO 287
Brightness		%ISO	92↑	92↑	92↑	92↑	92↑	92↑	ISO 2469
Opacity		%	92↑	92↑	94↑	95↑	97↑	98↑	ISO 2471
Roughness	W	µm	4.5±1	4.5±1	4.5±1	4.5±1	4.5±1	4.5±1	ISO 8791-4
	F		4.5±1	4.5±1	4.5±1	4.5±1	4.5±1	4.5±1	
Tensile Strength	MD	kh/15mm	7.0↑	7.0↑	8.0↑	9.0↑	12.0↑	18.0↑	ISO 1924
	CD		4.0↑	4.0↑	5.0↑	6.0↑	8.0↑	10.0↑	
Picking	W	A	≥10	≥10	≥10	≥10	≥10	≥10	T459
	F		≥10	≥10	≥10	≥10	≥10	≥10	

Note: The specification refers to an average of a composite sample according to our standard procedure.

Not to be used for purposes other than what we specified. We reserve the right to modifications.